## (19) World Intellectual Property Organization International Bureau





(43) International Publication Date 31 December 2003 (31.12.2003)

PCT

## (10) International Publication Number WO 2004/001671 A1

(51) International Patent Classification7: G01N 33/68, G06K 9/34

G06T 5/00.

(21) International Application Number:

PCT/SE2003/001060

(22) International Filing Date:

19 June 2003 (19.06.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 0201894-3

19 June 2002 (19.06.2002) SE


- (71) Applicant (for all designated States except US): LUDESI AB [SE/SE]; Växthuset Idéon, S-223 70 Lund (SE).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): WALLMARK, Gustav [SE/SE]; Gladstonevägen 3, S-224 56 Lund

(SE). HEYDEN, Anders [SE/SE]; Skogslyckevägen 9, S-240 10 Dalby (SE). KARLSSON, Andreas [SE/SE]; Trollebergsvägen 24A, S-222 29 Lund (SE). FORSSTRÖM-OLSSON, Ola [SE/SE]; Trastvägen 3, S-227 31 Lund (SE).

- (74) Agents: EK, Martin et al.; c/o Albihns Malmö AB, P.O. Box 4289, S-203 14 Malmö (SE).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: METHOD AND MEANS FOR 2D-GEL-IMAGE SEGMENTATION



(57) Abstract: The present invention relates to the segmentation of two-dimensional gel electrophoresis images (2D images). The method according to the invention associates an initial protein seed candidate with an interface circumscribing said seed and thereafter brings said interface to evolve in accordance with a defined speed function F(x, y). The evolution of the interface is halted by a stopping criterion, C. According to the invention, the speed function can depend on a wide variety of parameters such as the pixel intensity, the curvature of the pixel intensity, the distance to the initial seed, the curvature and/or shape and/or normal direction and/or position of the evolving interface. The stopping criterion depends e.g. on the speed function F and/or the time of arrival T(x, y) and/or the departure time  $T_{\rm aff}$  said interface. The invention provides criteria for a specific treatment of saturated spots and to make sure that interfaces never overlap.